

View Online at <https://aerobasegroup.com/nsn/5315-01-276-3480>

Head Diameter:

0.750 inches

Shank Diameter:

Between 0.3720 inches and 0.3745 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

4

Actuation Method:

Push button

Grip Length:

Between 1.400 inches and 1.420 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

18400 double pound

Shoulder To Head End Distance:

1.730 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

0.510 inches

Material:

Steel comp 4130 shank or steel comp 4135 shank

Material Specification:

Mil-s-6758 military specification 1st material response shank or mil-t-6736 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank

Surface Treatment:

Cadmium shank and chromate shank

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response shank

Style Designator:

Ring handle

Specification Data:

80205-nas1356 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.