

View Online at <https://aerobasegroup.com/nsn/5315-01-276-4983>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.369 inches

**Shoulder Diameter:**

0.375 inches

**Overall Length:**

1.437 inches

**First Step Diameter:**

Between 0.230 inches and 0.235 inches

**First Step Length:**

0.060 inches

**Second Step Diameter:**

Between 0.257 inches and 0.260 inches

**Second Step Length:**

0.100 inches

**Third Step Diameter:**

0.250 inches

**Third Step Length:**

0.369 inches

**Internal Drive Style:**

Slot

**Second End Slot Width:**

0.064 inches

**First End Taper Length:**

0.050 inches

**Second End Slot Depth:**

0.125 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Thread Size:**

0.250 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000, cond c military specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5000 spec.