

View Online at <https://aerobasegroup.com/nsn/5315-01-276-4983>

First End Style:

Chamfered

Second End Style:

Slotted

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.369 inches

Shoulder Diameter:

0.375 inches

Overall Length:

1.437 inches

First Step Diameter:

Between 0.230 inches and 0.235 inches

First Step Length:

0.060 inches

Second Step Diameter:

Between 0.257 inches and 0.260 inches

Second Step Length:

0.100 inches

Third Step Diameter:

0.250 inches

Third Step Length:

0.369 inches

Internal Drive Style:

Slot

Second End Slot Width:

0.064 inches

First End Taper Length:

0.050 inches

Second End Slot Depth:

0.125 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Thread Size:

0.250 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Material:

Steel comp e4340

Material Specification:

Mil-s-5000, cond c military specification single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.