

View Online at <https://aerobasegroup.com/nsn/5315-01-277-4506>

**Head Diameter:**

Between 1.175 inches and 1.330 inches

**Shank Diameter:**

Between 0.9970 inches and 0.9985 inches

**Ring Handle Diameter:**

1.640 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.800 inches and 1.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

147000 double pounds per square inch

**Shoulder To Head End Distance:**

2.000 inches

**Pin Attachment Type:**

Ring or link

**Detent To Tapered End Distance:**

Between 0.860 inches and 0.920 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6736 spec.