NSN 5315-01-277-5077

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-277-5077

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

0.875 inches

Detent Quantity:

2

Lanyard Length:

10.000 inches

Actuation Method:

Push button

Grip Length:

1.500 inches

Actuation Type:

Push

Shear Strength:

18400 double pound

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

Special Features:

One end chamfered 15.0 degrees min 30.0 degrees max

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle or cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 1 or type 2, cl 2 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

NSN 5315-01-277-5077

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-t-6736 spec.

