## NSN 5315-01-281-3463

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-281-3463 **Shank Diameter:** Between 0.3095 inches and 0.3120 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 4.000 inches and 4.020 inches **Actuation Type:** Push Hardness Rating: 40.0 rockwell c shank **Shear Strength:** 14400 double pound **Shoulder To Head End Distance:** 1.550 inches Pin Center To Handle End Distance: 1.780 inches Pin Attachment Type: Hook **Detent To Tapered End Distance:** 0.400 inches **Special Features:** Pushbutton incl release ring or retaining bail Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle or ams 5643 assn standard single material response spindle or ams 5520 assn standard single material response spindle or ams 5657 (non current) assn standard single material response spindle **Surface Treatment:** Passivate spindle **Style Designator:** L handle **Specification Data:** 80205-nas1335 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A212a0

No

## NSN 5315-01-281-3463

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.