## NSN 5315-01-281-5620

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-281-5620

| First End Style:  |
|---|
| Oval  |
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.703 inches  |
| Taper Length:   |
| 3.000 inches  |
| Taper Minor Diameter:   |
| Between 1.048 inches and 1.052 inches   |
| Hole Arrangement Style:   |
| One end drilled   |
| First Hole Diameter:  |
| Between 0.141 inches and 0.151 inches   |
| Distance From Centerline Of Hole To End Of Pin:   |
| 0.188 inches  |
| Grip Length:  |
| 2.750 inches  |
| Second End Relationship With First End:   |
| Identical   |
| Thread Size:  |
| 0.875 inches  |
| Taper:  |
| 0.516 per foot in inches  |
| First End Location:   |
| Both ends   |
| First End Outer Radius:   |
| 1.250 inches  |
| Material:   |
| Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130  |
| Material Specification:   |
| Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military |
| specification 3rd material response or mil-s-6758 military specification 4th material response  |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Qq-p-416, ty1 cl3 federal specification single treatment response   |
| Style Designator:   |
| Threaded at small end   |
| Thread Series Designator:   |

Unf

## NSN 5315-01-281-5620

Threaded Tapered Pin - Page 2 of 2



| Shalf | Life: |
|-------|-------|
| SHEII | LIIE. |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.