

View Online at <https://aerobasegroup.com/nsn/5315-01-282-5718>

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.000 inches and 1.020 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

8200 double pound

Shoulder To Head End Distance:

1.550 inches

Pin Center To Handle End Distance:

1.780 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.380 inches

Material:

Steel comp 4130 shank or steel comp 4135 shank

Material Specification:

Mil-s-6758 military specification 1st material response shank or mil-t-6736 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank

Surface Treatment:

Cadmium shank and chromate shank

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shank

Style Designator:

L handle

Specification Data:

80205-nas1334 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.