## NSN 5315-01-282-8269

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-282-8269 First End Style: Chamfered Second End Style: Oval **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.764 inches First Step Diameter: 1.250 inches First Step Length: 4.000 inches **Second Step Diameter:** Between 0.8105 inches and 0.8115 inches **Second Step Length:** 1.032 inches **Third Step Diameter:** 0.625 inches Third Step Length: 0.875 inches **Hole Arrangement Style:** Both end drilled First Hole Diameter: 0.187 inches **Second Hole Diameter:** 5.032 inches Distance From Centerline Of Hole To End Of Pin: 0.141 inches **Center To Center Distance Between Holes:** Between 0.6245 inches and 0.6250 inches First End Taper Length: 0.062 inches Second End Relationship With First End: Not identical **Thread Size:** 0.625 inches **First End Location:** Threaded end

First End Taper Angle: 45.0 degrees

## NSN 5315-01-282-8269

Headless Shoulder Pin - Page 2 of 2



Second End Outer Radius:	
0.688 inches	
Material:	
Steel comp 4130	
Material Specification:	
Mil-s-6758 military specification single material response	
Style Designator:	
Shoulder	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A212a0	
Mil-std (military Standard):	

Mil-s-6758 spec.