NSN 5315-01-282-9306

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-282-9306 First End Style: Countersunk **Head Style:** Flat chamfer **Under Head Length:** 2.218 inches First Step Diameter: Between 0.996 inches and 0.998 inches First Step Length: 0.906 inches **Second Step Diameter:** 0.748 mils and 0.749 centimeters Second Step Length: 1.250 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.375 inches and 0.376 inches Distance From Centerline Of Hole To End Of Pin: 0.781 inches **Hardness Rating:** 40.0 rockwell c and 45.0 rockwell c Pin Head Diameter: 1.312 inches **Surface Finish:** 32.0 microinches shoulder outside diameter **First End Countersink Diameter:** 0.187 inches **Special Features:** Undercut located between head and shoulder of pin; internal drive style on head of pin 0.625 inch pentagon Height: 0.187 inches Material: Steel comp 1042 or steel **Material Specification:** Aisi assn standard 1st material response or ordnance dwg 8853 ty c gr i cagec 10001 mfr ref 2nd material response **Style Designator:** Shoulder Shelf Life: N/a

--

Unit Of Measure:

NSN 5315-01-282-9306

Headed Shoulder Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0