NSN 5315-01-282-9306

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-282-9306

First End Style:
Countersunk
Head Style: Flat chamfer
Under Head Length: 2.218 inches
First Step Diameter:
Between 0.996 inches and 0.998 inches
First Step Length: 0.906 inches
Second Step Diameter: 0.748 mils and 0.749 centimeters
Second Step Length: 1.250 inches
Hole Arrangement Style: One end drilled
First Hole Diameter:
Between 0.375 inches and 0.376 inches
Distance From Centerline Of Hole To End Of Pin:
0.781 inches
Hardness Rating: 40.0 rockwell c and 45.0 rockwell c
Pin Head Diameter:
1.312 inches
Surface Finish:
32.0 microinches shoulder outside diameter
First End Countersink Diameter:
0.187 inches
Special Features:
Undercut located between head and shoulder of pin; internal drive style on head of pin 0.625 inch pentagon Height:
0.187 inches
Material:
Steel comp 1042 or steel
Material Specification:
Aisi assn standard 1st material response or ordnance dwg 8853 ty c gr i cagec 10001 mfr ref 2nd material response
Style Designator:
Shoulder Shelf Life:
N/a
Unit Of Measure:
-

NSN 5315-01-282-9306

Headed Shoulder Pin - Page 2 of 2

Demilitarization:

No

Fiig:

A212a0

