

View Online at <https://aerobasegroup.com/nsn/5315-01-285-2113>

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Button Handle Diameter:

Between 1.300 inches and 1.400 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Aircraft, viking s-3b; aircraft, hawkkeye e-2c; lav, anti-tank; helicopter, search and rescue, hh-60h; helicopter, seasprite h-2; helicopter, uscg search and rescue, hh-60j; helicopter, carrier based asw, sh-60f; aircraft, tomcat f-14; helicopter, sea king h-3

Grip Length:

Between 2.200 inches and 2.220 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

36800 double pound

Shoulder To Head End Distance:

1.190 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0