

View Online at <https://aerobasegroup.com/nsn/5315-01-286-1810>

Head Diameter:

Between 0.890 inches and 0.960 inches

Shank Diameter:

Between 0.7470 inches and 0.7485 inches

Ring Handle Diameter:

Between 1.312 inches and 1.500 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.500 inches and 3.520 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

73600 double pounds per square inch

Shoulder To Head End Distance:

1.250 inches

Pin Attachment Type:

Ring or link

Detent To Tapered End Distance:

0.790 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, ty2, cl 2 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.