

View Online at <https://aerobasegroup.com/nsn/5315-01-288-5820>

**Head Diameter:**

Between 0.655 inches and 0.755 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Ring Handle Diameter:**

1.125 inches

**Detent Quantity:**

2

**Grip Length:**

Between 2.800 inches and 2.820 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

36800 double megapascals

**Shoulder To Head End Distance:**

1.070 inches

**Detent To Tapered End Distance:**

0.590 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate handle

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response handle or qq-p-35 federal specification single treatment response handle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.