

View Online at <https://aerobasegroup.com/nsn/5315-01-293-0118>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

2.180 inches

**Shoulder Diameter:**

Between 0.432 inches and 0.434 inches

**Overall Length:**

4.540 inches

**First Step Diameter:**

Between 0.392 inches and 0.394 inches

**First Step Length:**

1.074 inches

**Second Step Diameter:**

0.375 inches

**Second Step Length:**

2.180 inches

**Third Step Diameter:**

Between 0.301 inches and 0.302 inches

**Third Step Length:**

0.880 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.125 inches and 0.129 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.620 inches and 0.625 inches

**Shoulder Length:**

1.074 inches

**Second End Slot Width:**

0.060 inches

**First End Taper Length:**

0.090 inches

**Second End Slot Depth:**

0.090 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**First End Location:**

Short shank end

**First End Taper Angle:**

60.0 degrees

**Surface Finish:**

63.0 microinches outside diameter

**Material:**

Steel comp 316

**Material Specification:**

Astm a276 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0