

View Online at <https://aerobasegroup.com/nsn/5315-01-293-5490>

Head Diameter:

Between 0.720 inches and 0.780 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Lanyard Length:

Between 9.750 inches and 10.250 inches

Actuation Method:

Push button

Grip Length:

Between 6.500 inches and 6.520 inches

Actuation Type:

Push

Shear Strength:

32800 double pound

Shoulder To Head End Distance:

1.820 inches

Pin Center To Handle End Distance:

2.000 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.530 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

Surface Treatment:

Cadmium spindle or cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416 type 1 cl 2 or cl 3 federal specification 1st treatment response spindle or qq-p-416 type 2 cl 2 or cl 3 federal specification 2nd treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.