

View Online at <https://aerobasegroup.com/nsn/5315-01-293-5490>

**Head Diameter:**

Between 0.720 inches and 0.780 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 9.750 inches and 10.250 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 6.500 inches and 6.520 inches

**Actuation Type:**

Push

**Shear Strength:**

32800 double pound

**Shoulder To Head End Distance:**

1.820 inches

**Pin Center To Handle End Distance:**

2.000 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.530 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

**Surface Treatment:**

Cadmium spindle or cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416 type 1 cl 2 or cl 3 federal specification 1st treatment response spindle or qq-p-416 type 2 cl 2 or cl 3 federal specification 2nd treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.