

View Online at <https://aerobasegroup.com/nsn/5315-01-295-8806>

First End Style:

Chamfered

Second End Style:

Chamfered and counterbored

Thread Length:

0.750 inches

Shank Length:

0.750 inches

Shoulder Diameter:

Between 2.3745 inches and 2.3750 inches

Shank Diameter:

Between 2.352 inches and 2.360 inches

Overall Length:

6.562 inches

Undercut Width:

0.125 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

0.344 inches

Distance From Centerline Of Hole To End Of Pin:

3.375 inches

Second End Taper Length:

0.125 inches

Thready Qty Per Inch (tpi):

18

Second End Relationship With First End:

Not identical

First End Location:

Threaded end

Surface Finish:

63.0 microinches shoulder outside diameter

Second End Taper Angle:

45.0 degrees

Special Features:

Drill 0.344 in. diameter 3.562 inch depth longitudinal hole in shoulder end, on axial center intersecting 0.344 inch diameter perpendicular hole, tap with 0.125 national pipe thread; two symmetrical grooves parallel to shoulder end 0.750 inch from end, 0.344 inch wide by 0.500 inch deep; keyway 0.312 inch wide 0.156 in. Nom depth 1.188 inches length with a full radius corner, on longitudinal centerline in shank; shank threaded for tn 12 timken locknut

Style Designator:

Undercut

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A212a0