

View Online at <https://aerobasegroup.com/nsn/5315-01-295-8806>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered and counterbored

**Thread Length:**

0.750 inches

**Shank Length:**

0.750 inches

**Shoulder Diameter:**

Between 2.3745 inches and 2.3750 inches

**Shank Diameter:**

Between 2.352 inches and 2.360 inches

**Overall Length:**

6.562 inches

**Undercut Width:**

0.125 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

0.344 inches

**Distance From Centerline Of Hole To End Of Pin:**

3.375 inches

**Second End Taper Length:**

0.125 inches

**Thready Qty Per Inch (tpi):**

18

**Second End Relationship With First End:**

Not identical

**First End Location:**

Threaded end

**Surface Finish:**

63.0 microinches shoulder outside diameter

**Second End Taper Angle:**

45.0 degrees

**Special Features:**

Drill 0.344 in. diameter 3.562 inch depth longitudinal hole in shoulder end, on axial center intersecting 0.344 inch diameter perpendicular hole, tap with 0.125 national pipe thread; two symmetrical grooves parallel to shoulder end 0.750 inch from end, 0.344 inch wide by 0.500 inch deep; keyway 0.312 inch wide 0.156 in. Nom depth 1.188 inches length with a full radius corner, on longitudinal centerline in shank; shank threaded for tn 12 timken locknut

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A212a0