NSN 5315-01-296-3026

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-296-3026 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.600 inches **Shank Length:** 1.600 inches **Shoulder Width Across Flats:** 1.500 inches **Shank Diameter:** 0.8750 inches **Overall Length:** Any acceptable **Undercut Diameter:** 0.770 inches **Undercut Width:** Between 0.130 inches and 0.170 inches First End Taper Length: 0.090 inches **Second End Taper Length:** Any acceptable Second End Relationship With First End: Not identical **Thread Size:** 0.8750 inches **Second Shank Diameter:** Between 1.057 inches and 1.067 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees **Second End Tip Radius:** 0.180 inches **Second End Taper Angle:** 30.0 degrees

Second Shank Length: Any acceptable

NSN 5315-01-296-3026

Headless Shoulder Pin - Page 2 of 2



Special Features:
Lubricant dry film surface treatment
Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Style Designator:
Undercut
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0