NSN 5315-01-296-6785

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-296-6785 First End Style: Chamfered Second End Style: Chamfered and counterbored **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.315 inches **Shank Length:** 0.315 inches **Shoulder Diameter:** 0.480 inches **Shank Diameter:** 0.375 inches **Overall Length:** 1.250 inches **Undercut Diameter:** Between 0.318 inches and 0.323 inches **Undercut Width:** Between 0.120 inches and 0.130 inches **Second End Counterbore Diameter:** 0.063 inches **Second End Counterbore Depth:** 0.063 inches First End Taper Length: 0.250 inches **Second End Taper Length:** 0.035 inches Second End Relationship With First End: Not identical **Thread Size:** 0.375 inches **Second Shank Diameter:** 0.188 inches **First End Location:** Unthreaded end **Second End Taper Angle:**

45.0 degrees

Second Shank Length:

0.750 inches

NSN 5315-01-296-6785

Headless Shoulder Pin - Page 2 of 2



| Surface Treatment: |
|---|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Undercut |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A212a0