## NSN 5315-01-296-7860

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-296-7860

| First End Style:   |
|--|
| Chamfered  |
| Second End Style:  |
| Radius   |
| Pinlength:   |
| Between 2.990 inches and 3.010 inches  |
| Pindiameter:   |
| Between 0.5001 inches and 0.5003 inches  |
| Second End Corner Radius:  |
| Between 0.063 inches and 0.167 inches  |
| First End Taper Length:  |
| 0.635 inches   |
| Second End Relationship With First End:  |
| Not identical  |
| Hardness Rating:   |
| 36.0 rockwell c and 42.0 rockwell c  |
| Shear Strength:  |
| 29000 double pound   |
| First End Taper Angle:   |
| Between 4.0 degrees and 16.0 degrees   |
| Surface Finish:  |
| 16.0 microinches outside diameter  |
| Material:  |
| Steel comp 416 or steel comp 410   |
| Material Specification:  |
| Astm a582 assn standard 1st material response or astm a493 assn standard 2nd material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Astm a380 assn standard single treatment response  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Filg:  |
| A212a0   |
|  |
|  |