## NSN 5315-01-296-8346

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-296-8346 **Head Diameter:** Between 0.600 inches and 0.800 inches **Shank Diameter:** 0.500 inches **Ring Handle Diameter:** 1.160 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** 0.020 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shoulder To Head End Distance:** 1.140 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** 0.460 inches **Special Features:** Handle material aluminum alloy qq-a-225/5 or qq-a-225/6; link material stainless steel qq-w-423 comp 302; balls material stainless steel cl 440c qq-s-763; pins rc c40 min Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Qq-w-423 federal specification single material response ring **Surface Treatment:** Cadmium spring and passivate spring **Surface Treatment Specification:** Qq-p-416 ty ii cl 2 federal specification 1st treatment response spindle or cqq-p-35 federal specification 2nd treatment response spindle **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:** 

No **Fiig:** 

A212a0

**Demilitarization:** 

## NSN 5315-01-296-8346

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.