# NSN 5315-01-296-8346

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-296-8346

#### Head Diameter:

Between 0.600 inches and 0.800 inches

#### Shank Diameter:

0.500 inches

# **Ring Handle Diameter:**

1.160 inches

#### **Detent Quantity:**

2

# Actuation Method:

Push button

Grip Length:

0.020 inches

#### **Actuation Type:**

Push

#### Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

# Shoulder To Head End Distance:

1.140 inches

# Pin Attachment Type:

Link or ring

# **Detent To Tapered End Distance:**

0.460 inches

# **Special Features:**

Handle material aluminum alloy qq-a-225/5 or qq-a-225/6; link material stainless steel qq-w-423 comp 302; balls material stainless steel cl

440c qq-s-763; pins rc c40 min

#### Material:

Steel comp 630 spindle or steel comp 632 spindle

#### **Material Specification:**

Qq-w-423 federal specification single material response ring

#### Surface Treatment:

Cadmium spring and passivate spring

#### Surface Treatment Specification:

Qq-p-416 ty ii cl 2 federal specification 1st treatment response spindle or cqq-p-35 federal specification 2nd treatment response spindle

#### Style Designator:

Ring handle

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A212a0

# NSN 5315-01-296-8346

Quick Release Pin - Page 2 of 2

# Mil-std (military Standard):

Mil-a-8625 spec.

