

View Online at <https://aerobasegroup.com/nsn/5315-01-297-8345>

**Head Style:**

Hexagon

**Overall Length:**

2.020 inches

**Offset Distance Between Geometric Center Of Head And Centerline Of Shank/shoulder:**

0.050 inches

**First Step Diameter:**

Between 1.122 inches and 1.124 inches

**First Step Length:**

0.400 inches

**Second Step Diameter:**

Between 0.874 inches and 0.875 inches

**Second Step Length:**

Between 1.360 inches and 1.370 inches

**Numeric Designation Of Step Eccentric To Head:**

2

**Width Across Flats:**

1.250 inches

**Special Features:**

One groove 0.046 inch min 0.049 inch maximum wide, 0.818 inch min 0.824 inch maximum diameter, located 1.760 inches min 1.770 inches maximum from bearing surface of head; keyway on shank end parallel with eccentric offset 0.128 inch nom wide, 0.500 inch nom long, 0.061 inch 0.062 inch depth with a full radius

**Height:**

0.120 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond d-4 military specification single material response

**Style Designator:**

Eccentric

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.