

View Online at <https://aerobasegroup.com/nsn/5315-01-298-2845>

**First End Style:**

Chamfered and counterbored

**Pinlength:**

3.000 inches

**Pindiameter:**

0.5000 inches

**First End Counterbore Diameter:**

0.360 inches

**Second End Counterbore Diameter:**

0.360 inches

**First End Counterbore Depth:**

0.600 inches

**Second End Counterbore Depth:**

0.600 inches

**First End Taper Length:**

Between 0.063 inches and 0.167 inches

**Second End Taper Length:**

Between 0.063 inches and 0.167 inches

**Second End Relationship With First End:**

Identical

**First End Taper Angle:**

Between 20.0 degrees and 30.0 degrees

**Second End Taper Angle:**

Between 20.0 degrees and 30.0 degrees

**Material:**

Steel

**Material Specification:**

S16556-683 military standard 10th material response or stma582, type 416, cond a assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Test Data Document:**

18876-12333945 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0