

View Online at <https://aerobasegroup.com/nsn/5315-01-298-7813>

First End Style:

Chamfered

Second End Style:

Round

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Shank Length:

1.120 inches

Shoulder Diameter:

Between 0.365 inches and 0.375 inches

Shank Diameter:

0.250 inches

Overall Length:

2.120 inches

First End Taper Length:

0.060 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Outer Radius:

0.188 inches

Special Features:

Two symmetrical flats 0.500 in. Nom lg 0.312 in. Nom w across on shoulder adjacent with thread runout

Material:

Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 420 or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446 or steel comp 633 or steel comp 634 or stainless steel

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0