## NSN 5315-01-298-7813

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-298-7813
First End Style:
Chamfered
Second End Style:
Round
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Shank Length:
1.120 inches
Shoulder Diameter:
Between 0.365 inches and 0.375 inches
Shank Diameter:
0.250 inches
Overall Length:
2.120 inches
First End Taper Length:
0.060 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second End Outer Radius:
0.188 inches
Special Features:
Two symmetrical flats 0.500 in. Nom lg 0.312 in. Nom w across on shoulder adjacent with thread runout
Material:
Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel
comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp
403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 420 or steel comp 431 or steel comp 440a or steel comp 440b
or steel comp 440c or steel comp 446 or steel comp 633 or steel comp 634 or stainless steel
Material Specification:
Qq-s-763 federal specification all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:

Shoulder

Style Designator:

Qq-p-35 federal specification single treatment response

## NSN 5315-01-298-7813

Headless Shoulder Pin - Page 2 of 2



Thread	<b>Series</b>	Designator:

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0