# NSN 5315-01-299-4638

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-299-4638

#### Head Diameter:

Between 0.215 inches and 0.225 inches

#### Shank Diameter:

Between 0.1870 inches and 0.1885 inches

#### **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

## **Detent Quantity:**

2

#### **Actuation Method:**

Push button

Grip Length:

Between 1.600 inches and 1.620 inches

# Actuation Type:

Pull and push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shear Strength:

5150 double pounds per square inch

#### Shoulder To Head End Distance:

0.935 inches

## Pin Attachment Type:

Link or ring

## **Detent To Tapered End Distance:**

0.410 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

#### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A212a0