

View Online at <https://aerobasegroup.com/nsn/5315-01-300-6455>

First End Style:

Chamfered

Second End Style:

Threaded and counterbored

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.798 inches

First Step Length:

0.250 inches

Second Step Diameter:

Between 0.7485 inches and 0.7491 inches

Second Step Length:

3.332 inches

Third Step Diameter:

0.625 inches

Third Step Length:

0.798 inches

Second End Counterbore Diameter:

0.625 inches

Second End Counterbore Depth:

0.400 inches

First End Taper Length:

0.060 inches

Second End Taper Length:

0.060 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.625 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Taper Angle:

45.0 degrees

First Step Width Across Flats:

0.880 inches

Special Features:

Hole through longitudinal center 0.185 in. Min. Dia. 0.190 in. Max. Dia., 1.500 in. Deep; second shank has a hole 0.125 in. Dia. 0.440 in.

Deep along axial which is interceptive by first hole

Material:

Steel comp 1045

Material Specification:

296400ca cagec 06889 mfr ref single material response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0