NSN 5315-01-301-6713

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-301-6713 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.310 inches and 0.312 inches **Ring Handle Diameter:** 1.200 inches **Detent Quantity: Actuation Method:** Handle **Grip Length:** 0.700 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature **Hardness Rating:** 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 12800 double pound **Shoulder To Head End Distance:** 1.290 inches Pin Attachment Type: Hook **Detent To Tapered End Distance:** 0.680 inches Material: Steel shank **Material Specification:** Mil-t-6732 military specification 1st material response head or mil-s-6758 military specification 1st material response head **Surface Treatment:** Cadmium shank **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification 2nd treatment response shank **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5315-01-301-6713

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.