## NSN 5315-01-302-2061

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-302-2061 **Head Diameter:** 0.940 inches **Shank Diameter:** Between 0.4970 inches and 0.4995 inches **Ring Handle Diameter:** 1.370 inches **Actuation Method:** Push button **Grip Length:** Between 2.700 inches and 2.720 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature Hardness Rating: 54.0 rockwell c detent and 64.0 rockwell c detent **Shoulder To Head End Distance:** 2.180 inches Pin Attachment Type: Hook **Detent To Tapered End Distance:** 0.590 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1358 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A212a0

## NSN 5315-01-302-2061

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.