## NSN 5315-01-303-2484

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-303-2484

## Head Diameter: 0.750 inches Shank Diameter: Between 0.2470 inches and 0.2495 inches **Ring Handle Diameter:** 1.220 inches **Actuation Method:** Push button Grip Length: Between 0.700 inches and 0.720 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature Hardness Rating: 54.0 rockwell c detent and 64.0 rockwell c detent **Shoulder To Head End Distance:** 1.730 inches **Pin Attachment Type:** Hook or ring **Detent To Tapered End Distance:** 0.410 inches Material: Steel comp 4130 spindle Material Specification: Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response spindle Style Designator: Ring handle **Specification Data:** 80205-nas1354 professional/industrial association standard Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A212a0

## NSN 5315-01-303-2484

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.

