

View Online at <https://aerobasegroup.com/nsn/5315-01-303-3961>

**First End Style:**

Radius

**Shank Length:**

Between 0.265 inches and 0.275 inches

**Shoulder Diameter:**

Between 0.5763 inches and 0.5768 inches

**Shank Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

Between 2.890 inches and 2.900 inches

**First End Corner Radius:**

0.040 inches

**Second End Relationship With First End:**

Identical

**Second Shank Diameter:**

Between 0.4995 inches and 0.5000 inches

**First End Location:**

Both ends

**Second Shank Length:**

Between 0.355 inches and 0.375 inches

**Special Features:**

Apply solid film lubricant per ef98 edo report 5370, 0.0003 -0.0005 thick per surface over dimensions shown

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629, cond h-1000 assn standard single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Qq-c-320, class 2d, 0.0002-0.0004 thickness federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0