

View Online at <https://aerobasegroup.com/nsn/5315-01-303-8189>

First End Style:

Chamfered

Head Style:

Thumb no. 3

Under Head Length:

Between 1.840 inches and 1.920 inches

First Step Diameter:

Any acceptable

First Step Length:

Between 0.650 inches and 0.730 inches

Second Step Diameter:

Between 0.450 inches and 0.468 inches

Second Step Length:

1.190 inches

Head Width:

Any acceptable

Hole Arrangement Style:

Drilled through head

First Hole Diameter:

Between 0.368 inches and 0.382 inches

Distance From Centerline Of Hole To End Of Pin:

1.740 inches

First End Taper Length:

0.100 inches

First End Taper Angle:

45.0 degrees

Special Features:

Symmetrical flats 0.760 inch wide on shoulder places; groove 0.750 inch diameter 0.220 inch long adjoining head

Height:

Any acceptable

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 1 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.