## NSN 5315-01-303-8189

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-303-8189 First End Style: Chamfered **Head Style:** Thumb no. 3 **Under Head Length:** Between 1.840 inches and 1.920 inches First Step Diameter: Any acceptable First Step Length: Between 0.650 inches and 0.730 inches **Second Step Diameter:** Between 0.450 inches and 0.468 inches Second Step Length: 1.190 inches **Head Width:** Any acceptable **Hole Arrangement Style:** Drilled through head First Hole Diameter: Between 0.368 inches and 0.382 inches **Distance From Centerline Of Hole To End Of Pin:** 1.740 inches First End Taper Length: 0.100 inches First End Taper Angle: 45.0 degrees **Special Features:** Symmetrical flats 0.760 inch wide on shoulder places; groove 0.750 inch diameter 0.220 inch long adjoining head Height: Any acceptable Material: Steel comp 4130 **Material Specification:** Mil-s-6758 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 1 federal specification single treatment response **Style Designator:** Shoulder

N/a

Shelf Life:

## NSN 5315-01-303-8189

Headed Shoulder Pin - Page 2 of 2



	• •						
ın	18	Of	ΝЛ	ດລ	CI.	ır	ο.

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.