

View Online at <https://aerobasegroup.com/nsn/5315-01-303-8825>

Head Diameter:

Between 0.640 inches and 0.755 inches

Shank Diameter:

Between 0.4970 inches and 0.4995 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Lanyard Length:

Between 5.500 inches and 6.500 inches

Actuation Method:

Push button

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

32000 double pound

Shoulder To Head End Distance:

1.000 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.590 inches

Special Features:

Cable steel, comp 302 or 303, mil-w-83420, comp b, type 1; vinyl coating mil-i-631, type f; includes 2 sleeves ms51844-62 or ms51844-22 and end clip

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.