

View Online at <https://aerobasegroup.com/nsn/5315-01-303-8826>

Head Diameter:

Between 0.720 inches and 0.780 inches

Handle Length:

Between 2.250 inches and 2.500 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Lanyard Length:

Between 11.750 inches and 12.250 inches

Actuation Method:

Push button

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

32800 double pound

Shoulder To Head End Distance:

1.820 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.530 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-5758 military specification single material response spindle or mil-t-6736 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-5758 spec.