## NSN 5315-01-303-9711

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-303-9711 **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Button Handle Diameter:** 1.300 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 1.500 inches and 1.520 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shear Strength:** 36800 double pounds per square inch **Shoulder To Head End Distance:** 1.160 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 1.070 inches and 1.100 inches **Special Features:** Handle dyed dark gray or black; push button dyed blue Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Qq-a-225/6 federal specification 1st material response handle or qq-a-225/5 federal specification 2nd material response handle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator: Button** Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

A212a0

**Demilitarization:** 

## NSN 5315-01-303-9711

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.