NSN 5315-01-304-2850

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-304-2850 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Ring Handle Diameter:** 1.220 inches **Actuation Method:** Push button **Grip Length:** Between 2.600 inches and 2.620 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature Hardness Rating: 54.0 rockwell c detent and 64.0 rockwell c detent **Shoulder To Head End Distance:** 1.730 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.410 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1354 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A212a0

NSN 5315-01-304-2850

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.