NSN 5315-01-304-5382



Headed Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-304-5382 First End Style: Chamfered **Head Style:** Flat **Under Head Length:** 5.000 inches First Step Diameter: Between 0.737 inches and 0.747 inches First Step Length: 1.500 inches **Second Step Diameter:** Between 0.495 inches and 0.497 inches Second Step Length: 3.500 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.096 inches and 0.116 inches Distance From Centerline Of Hole To End Of Pin: 0.375 inches First End Taper Length: 0.060 inches **Hardness Rating:** 35.0 rockwell c and 39.0 rockwell c First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.250 inches Height: 0.250 inches Material: Steel comp 4130 or steel comp 4137 or steel comp 4140 or steel comp 4142 or steel comp 4145 or steel comp 4147 or steel comp 4150 **Material Specification:** Astm a322 assn standard all material responses or astm a331 assn standard all material responses **Surface Treatment:** Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

NSN 5315-01-304-5382

Headed Shoulder Pin - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A212a0