## NSN 5315-01-304-6933

Quick Release Pin - Page 1 of 1

Fiig: A212a0



View Online at https://aerobasegroup.com/nsn/5315-01-304-6933 **Shank Diameter:** Between 0.3700 inches and 0.3730 inches **Ring Handle Diameter:** 1.187 inches **Detent Quantity: Grip Length:** Between 0.800 inches and 0.820 inches **Actuation Type:** Push Hardness Rating: 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 10300 double pounds per square inch Pin Attachment Type: Ring **Detent To Tapered End Distance:** 0.390 inches **Special Features:** Includes lanyard, stainless steel w/vinyl covering; 4.000 in. Lg; pressed loop one end; tab other end w/0.129 in. Diameter hole Material: Steel comp 302 shank or steel comp 304 shank or steel comp 304 shank or steel comp 305 shank or steel comp 309 shank or steel comp 310 shank or steel comp 316 shank or steel comp 316 shank or steel comp 317 shank or steel comp 321 shank or steel comp 347 shank **Material Specification:** Qq-s-763 federal specification all material responses shank **Surface Treatment:** Passivate shank **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response shank **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:** Demilitarization: No