# NSN 5315-01-304-6937

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-304-6937

### Head Diameter:

0.980 inches

#### Shank Diameter:

Between 0.8720 inches and 0.8735 inches

## **Ring Handle Diameter:**

1.640 inches

#### **Detent Quantity:**

2

### **Actuation Method:**

Push button

Grip Length:

Between 4.000 inches and 4.020 inches

### Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c spindle

### Shear Strength:

112500 double pound

### Shoulder To Head End Distance:

1.875 inches

# Pin Attachment Type:

Hook or ring

## Detent To Tapered End Distance:

Between 1.041 inches and 1.051 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

### Surface Treatment:

Passivate spindle

### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### **Style Designator:**

Ring handle

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A212a0