

View Online at <https://aerobasegroup.com/nsn/5315-01-305-7678>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Shank Length:**

4.640 inches

**Shoulder Diameter:**

1.500 inches

**Shank Diameter:**

Between 0.740 inches and 0.742 inches

**Overall Length:**

6.780 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.165 inches and 0.172 inches

**Second Hole Diameter:**

Between 0.165 inches and 0.172 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.200 inches

**Center To Center Distance Between Holes:**

6.130 inches

**First End Taper Length:**

0.060 inches

**Second End Taper Length:**

0.190 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

30.0 rockwell c and 35.0 rockwell c

**Second Shank Diameter:**

Between 0.745 inches and 0.755 inches

**First End Location:**

Short shank end

**First End Taper Angle:**

45.0 degrees

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

1.640 inches

**Material:**

Steel comp 4130 or steel comp 4140

**Material Specification:**

Astm a322 assn standard all material responses or astm a331 assn standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0