NSN 5315-01-306-1652

Headless Shoulder Pin - Page 1 of 2



group.com/nsn/5315-01-306-1652

| View Online at https://aerobasegroup.com/ns |
|---|
| First End Style: |
| Chamfered |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.380 inches |
| Shank Length: |
| 0.380 inches |
| Shoulder Diameter: |
| 0.500 inches |
| Shank Diameter: |
| 0.375 inches |
| Overall Length: |
| 3.750 inches |
| First End Taper Length: |
| 0.060 inches |
| Second End Relationship With First End: |
| Identical |
| Thread Size: |
| 0.375 inches |
| First End Location: |
| Chamfered end |
| First End Taper Angle: |
| |

45.0 degrees

Special Features:

Finish color black

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-f-13924 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

NSN 5315-01-306-1652

Headless Shoulder Pin - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-13924 spec.