NSN 5315-01-306-2462

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-306-2462 **Shank Diameter:** Between 0.4970 inches and 0.4995 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 2.500 inches and 2.520 inches **Actuation Type:** Push Hardness Rating: 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 32800 double pound **Shoulder To Head End Distance:** 1.820 inches Pin Center To Handle End Distance: 2.000 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** 0.530 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator:** L handle **Specification Data:** 80205-nas1338 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A212a0

NSN 5315-01-306-2462

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.