

View Online at <https://aerobasegroup.com/nsn/5315-01-306-9690>

**First End Style:**

Square

**Head Style:**

Flat fillister

**Diameter:**

Between 0.245 inches and 0.255 inches

**Effective Length:**

Between 0.574 inches and 0.576 inches

**Undercut Diameter:**

Between 0.210 inches and 0.212 inches

**Under Head Length:**

Between 1.282 inches and 1.302 inches

**Undercut Width:**

Between 0.029 inches and 0.032 inches

**Pin Head Diameter:**

Between 0.580 inches and 0.600 inches

**Special Features:**

Protrusion on one side of head 0.080 in. Min and 0.100 in. Maximum height, 0.050 in. Min and 0.070 in. Maximum width; agavgadvanced medium range air to air missile/lau 129a, end chamfered 45 degrees, flat edge 0.0675 in.

**Height:**

Between 0.290 inches and 0.310 inches

**Material:**

Aluminum alloy 356.0 or aluminum alloy 6061

**Material Specification:**

Ams 4260, t6 assn standard single material response or qq-a-225/8, t651 federal standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type ii, class 1 military specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.