NSN 5315-01-307-3670

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-307-3670

| Handle Length: |
|--|
| Between 1.750 inches and 1.815 inches |
| Shank Diameter: |
| Between 0.1870 inches and 0.1885 inches |
| Detent Quantity: |
| 2 |
| Actuation Method: |
| Push button |
| Grip Length: |
| Between 0.800 inches and 0.820 inches |
| Actuation Type: |
| Push |
| Hardness Rating: |
| 40.0 rockwell c spindle |
| Shear Strength: |
| 5150 double pound |
| Shoulder To Head End Distance: |
| 1.270 inches |
| Pin Attachment Type: |
| Link or ring |
| Detent To Tapered End Distance: |
| Between 0.230 inches and 0.260 inches |
| Material: |
| Steel comp 630 spindle or steel comp 632 spindle |
| Material Specification: |
| Ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle |
| Surface Treatment: |
| Passivate spindle |
| Surface Treatment Specification: |
| Qq-p-35 federal specification all treatment responses shank |
| Style Designator: |
| T handle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Δ212a0 |