

View Online at <https://aerobasegroup.com/nsn/5315-01-307-8681>

**First End Style:**

Square

**Head Style:**

Square

**Under Head Length:**

Between 1.310 inches and 1.350 inches

**First Step Diameter:**

Between 0.146 inches and 0.166 inches

**First Step Length:**

Between 0.810 inches and 0.850 inches

**Second Step Diameter:**

Between 0.142 inches and 0.145 inches

**Second Step Length:**

Between 0.480 inches and 0.520 inches

**Head Width:**

Between 0.220 inches and 0.260 inches

**Hole Arrangement Style:**

Drilled through head

**First Hole Diameter:**

Between 0.086 inches and 0.106 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 1.403 inches and 1.443 inches

**Special Features:**

0.040 in. Min. 0.080 in. Max. Taper length two places on head of pin; 0.029 in. Min. 0.032 in. Max. Wide undercut 0.116 in. Min. 0.118 in.

Max. Dia. Undercut located near second step end

**Height:**

Between 0.180 inches and 0.220 inches

**Material:**

Steel

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0