# NSN 5315-01-310-3748

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-310-3748

## Shank Diameter:

Between 0.1870 inches and 0.1895 inches

### **Detent Quantity:**

2

## Actuation Method:

Push button

#### Grip Length:

Between 1.190 inches and 1.210 inches

#### **Actuation Type:**

Push

#### Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

#### Shear Strength:

4600 double pounds per square inch

## Shoulder To Head End Distance:

1.550 inches

## Pin Center To Handle End Distance:

1.780 inches

## **Pin Attachment Type:**

Hook or ring

## Detent To Tapered End Distance:

0.380 inches

## Material:

Steel comp 4130 spindle

## **Material Specification:**

Mil-s-6758 military standard single material response spindle

## Surface Treatment:

Cadmium spindle and chromate spindle

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

## Style Designator:

L handle

## **Specification Data:**

80205-nas1333 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A212a0

# NSN 5315-01-310-3748

Quick Release Pin - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6758 spec.

